

BV Series

Specifications

BV5160 SC-14 - BV5160 NET



| Kubota Models | BV5160 SC14 | BV5160NET |
|---|---------------------|---------------------|
| Weight and Dimensions | | |
| Length (in) | 176" | |
| Width (in) | 99" | |
| Height (in) | 106" | |
| Weight (lbs) | 7165 | 6965 |
| Bale chamber | | |
| Diameter Min (in) | 24" | |
| Diameter Max (in) | 65" | |
| Bale Width(in) | 47" | 47" |
| Bale Height(in) | 60" | 60" |
| Bale Formation | 5 Belts + 3 Rollers | 5 Belts + 3 Rollers |
| Endless Belts | • | • |
| Bale Ramp | • | • |
| Pick-up | | |
| Working Width (in) | 86" | |
| Number of Tine Rows | 5 | 5 |
| Tine Spacing (in) | 2.36" | |
| Windguard | Roller Wind Guard | |
| Pneumatic Gauge Wheel | • | |
| Flare to Flare Pickup | | 86" |
| Lift | | Hydraulic |
| Pickup Protection | | Radial Clutch |
| Intake System | | |
| Fork Feeder | - | |
| Protection, cam clutch | - | |
| SuperCut-14 Knives | • | |
| Single Knife Protection | • | |
| Unblocking System | Drop Floor | |
| Driveline | | |
| Chain | 1.25" | 1.25" |
| 1 1/4" Main drive chain | • | |
| Wide angle PTO Shaft | • | |
| Shear Bolt Protection | - | |
| Cam Clutch Protection | • | |
| Binding | | |
| Binding | Net/Twine | Net |
| Monitor | Focus | Focus |
| Twine | double arm | NA |
| Operations | | |
| ISOBUS | • | |
| Focus Terminal | • | |
| IsoMatch Tellus | o | |
| Hydraulic Outlets | 1SA + 1DA | |
| Wheels and Axles | | |
| 11.5/80-15 | - | |
| 15.0/55-17 | • | |
| 19.0/45-17 | o | |
| 500/45-22.5 | o | |
| Others | | |
| PTO (rpm) | | 540CV |
| PTO Protection | | CamClutch |
| Minimum Horsepower (hp) | | 75 |
| Tires | | 31x13.5x15 |
| • = standard o = optional - = not available | | |

The company reserves the right to change the above specifications without notice. This brochure is for descriptive purpose only. Some of the items pictured in this brochure are optional and not standard equipment. Please consult your local Kubota dealer for warranty, safety or product information. For your safety, Kubota strongly recommend the use of a seat belt in all applications.