

DM5000

Specifications

DM5032 - DM5040



Kubota Models	DM5032	DM5040
Dimensions and Weight		
Cutting Width (ft)	10'6"	13'1"
Weight, approx. (lbs)	2256	2513
Transport Width (ft)	9'10"	12'5"
Attachment to Tractor		
Hitch (CAT)	2	2
Pin hitch	•	•
PTO (RPM)	540/1000	540/1000
Minimum PTO horsepower required (hp)	65	85
Operation		
Number of disc and knives	8 / 24	10 / 30
Remotes	2	2
Cutterbar operating angle	-17 / +17	-17 / +17
Stubble height (in)	1.79"-3.94"	1.79"-3.94"
Other Features		
BreakAway	-	-
Non-Stop BreakAway	-	-
Overrun clutch	•	•
Friction clutch	•	•
Optional Equipment		
Swath Board (RH/LH)	-	-
Swath Rollers (RH/LH)	o / o	o / o
High skids (inches) +0.8 / +1.6 / +3.2	• / o / o	• / o / o
Lighting kit	•	•
• = standard o = optional - = not available		

The company reserves the right to change the above specifications without notice. This brochure is for descriptive purpose only. Some of the items pictured in this brochure are optional and not standard equipment. Please consult your local Kubota dealer for warranty, safety or product information. For your safety, Kubota strongly recommend the use of a seat belt in all applications.