

FARMALL® A SERIES TRACTORS



THERE'S A LOT OF WORK AHEAD OF YOU. YOU WANT TO CUT STEPS, CUT COSTS... NOT CORNERS. WILL YOU BE READY?

Sometimes it might seem there's no end to the work that's waiting for you. But while the tasks ahead may seem unlimited, the resources to do them never are. Here are the machines to help you get it all done, without busting your schedule or your budget: The new Farmall A series tractors from Case IH. All four models deliver the power and performance you need, reliably and cost-effectively. Like you, these scrappy utility tractors aren't afraid of a little hard work.

BE READY.

PERFORMANCE

The Farmall heritage of performance goes all the way back to 1923, when the first Farmall rolled off the line and changed the way America works forever. The new Farmall A series builds on that tradition with performance features that go way beyond what you might expect.

VALUE

Value doesn't mean cheap. It means getting the most for your buck. And that's what the cost-competitive Farmall A series tractors offer. Check out the specs and the features, then see what the competition offers dollar-for-dollar, feature-for-feature, here's real tractor value.

VERSATILITY

You have to be ready for any chore that comes up, and you expect the same from your utility tractor. From loader work to mowing to blading, your Farmall A series tractor is one versatile all-around workhorse.

OPERATOR ENVIRONMENT

The work is tough. The hours are long. Out here in the real world, operator comfort is no luxury – it's an absolute necessity. To help you stay productive day after day, Farmall A series tractors offer a smooth ride with a comfortable seat and ergonomic, intuitive controls that lets any operator work all day in easy-riding comfort.

PERFORMANCE

4-5

VALUE

6

VERSATILITY

7

OPERATOR ENVIRONMENT

8-9

LOADERS

10

PRODUCT SPECIFICATIONS

11



UTILITY TRACTOR PERFORMANCE THAT GOES ABOVE AND BEYOND

Here's how you can get top-notch performance from a utility tractor without sacrificing value; check out the Farmall A tractors from Case IH. These scrappy performers offer everything you want in a basic utility tractor, and more. We designed these no-nonsense machines for smaller acreage farms, rural estates, and municipal applications, as well as for commercial users who need a reliable, efficient tractor.

And then we added performance features, taking every aspect just a step further. For instance, we equip every Farmall A tractor with standard features you might not expect on a utility machine – like a 3-point hitch with flexible link ends, a folding ROPS and a rear remote. That's performance above and beyond expectations.

THE PERFORMANCE STARTS NOW

Here's where it all begins: under the hood. All four Farmall A tractors feature proven Tier III engines that deliver more power and torque while respecting the environment. These powerful turbocharged engines feature parent bore engine block design for stability, as well as a reliable mechanical fuel injection system. They all offer excellent fuel efficiency and a specially-designed exhaust system that directs noise and fumes away from the operator and the ground.

WORKING TO A HIGHER STANDARD

Forget what you know about “basic utility tractors.” Case IH Farmall A tractors offer more standard features for better performance. For instance, our standard 3-point hitch gives you flexible link ends for easy implement attachment, and telescopic stabilizers to keep those implements steady. Up to 540 rpm PTO – fully independent to power your implements. And you can take all these other “extras” for granted, too: Standard planetary final drive rear axle, rugged construction for long service life, independent hydraulic flow to implements, and one rear remote for easy hookup of hydraulic tools.



PICK A MODEL – ANY MODEL

Every Farmall A tractor is built with proven basics for simple operation and rugged reliability. That means a tough, trouble-free 4-cylinder diesel engine that's dependable and fuel efficient. It means a simple, straightforward mechanical transmission that's easy to operate. And it includes plenty of pulling power and hydraulics for loading, blading, tilling, mowing and baling chores. Plus, every Farmall A tractor is available in either 2WD or 4WD, to deliver all the traction and power you need for your operation. That's the sort of performance you have a right to expect.

| MODEL | GROSS ENGINE HP | PTO HP | AXLE | TRANSMISSION |
|-------------|-----------------|--------|-----------|--------------|
| FARMALL 45A | 45 | 39 | 2WD / MFD | 8 x 8 |
| FARMALL 55A | 55 | 47.5 | 2WD / MFD | 8 x 8 |
| FARMALL 65A | 65 | 57 | 2WD / MFD | 8 x 2 |
| FARMALL 75A | 75 | 66 | 2WD / MFD | 8 x 2 |

REAL VALUE MEANS GETTING THE MOST TRACTOR YOU CAN FOR YOUR DOLLAR

To be a genuine value, your utility tractor can't scrimp where it matters most – toughness and durability, power and performance. The key is having the expertise and engineering know-how to design a machine that offers bottom-line economy without compromising quality. That's where the Farmall DNA shines through. That's a hardworking heritage that goes back to 1923, a tradition that makes the Farmall name a legend to generations of hard-to-please farmers without a nickel to waste. They know that real value means making every dollar work as hard as you do.

Case IH Farmall A tractors include a rich array of performance features that make them worth more on the job – whatever the job happens to be.



THREE-POINT HITCH

There's no value at all in a tractor that slows down chores. So all four Farmall A models include a 3-point hitch with flexible links that make it faster and easier to attach implements.



STANDARD REMOTE VALVE

Why should you pay extra for a feature that ought to be standard equipment? One remote valve is standard on all Farmall A tractors.

FOUR TOUGH UTILITY TRACTORS: COUNTLESS WAYS TO USE THEM.

The Farmall A tractors from Case IH are such valuable performers because they make themselves useful in a variety of applications. With their standard 3-point hitch, remote valve, and 540 rpm PTO, you can attach and power a range of tools and implements, depending on what you need done. Hydrostatic steering means effortless operation and outstanding maneuverability, while the intuitive controls are simple enough for even inexperienced operators to learn to handle with ease.*

Whichever model you select, your Farmall A will be your go-to worker when it comes to loading, blading, tilling, mowing and baling chores.



VERSATILITY IS THE NORM

Farmall A series tractors are specifically designed to meet your needs when performing cutting, baling, pulling various tools and moving material with the strong L500 series loaders.



CUT THE TIME IT TAKES

Whether you're mowing a right-of-way or a woodlot, your Farmall A tractor offers reliable power and easy handling to make the job go faster.



YOU'VE GOT A FRIEND WITH PULL

Talk about a workhorse: Farmall A tractors feature trouble-free, fuel-efficient 4-cylinder diesel engines and simple, straightforward mechanical transmissions.

*Always read the Operator's Manual before operating the tractor.

OUT HERE, COMFORT IS A NECESSITY

Out on the job, day after grueling day, it's a hard life for machine and operator alike. Out here, comfort isn't a luxury – it's the only way to keep working all day long under tough conditions. The Case IH Farmall A tractors are designed with hardworking operators in mind. Our comfortable operator platform is built larger, with low vibration levels. The seat is fully adjustable to fit every operator, and the essential controls are right at your fingertips. Operator comfort might seem like an extra to some folks, but with a Case IH Farmall A series tractor, it's all in a day's work.



WHEN THE GOING GETS TIGHT

With standard folding ROPS and easy maneuverability, Farmall A tractors aren't above doing the hard jobs even in the closest quarters.



INCREASE THE VERSATILITY OF YOUR FARMALL A TRACTOR

These robust loaders are designed specifically to match Farmall A tractors. They install and remove in minutes, and let you switch easily between attachments. That saves time and lets you handle a variety of tough tasks with maximum efficiency. No tools are required for attachment, since each is designed around a quick-attach loader frame. Implement hook-up is quick and easy, too. The front guard protects tractor grill during loader operations – and a front grill guard can be mounted without the loader for everyday protection.



THE FARMALL 45A AND 55A MODELS USE THE L530 FRONT LOADER

2,624 lb. (1190 kg) lift capacity @ pivot pins
111 in. (2820 mm) lift height
4,299 lb. (1950 kg) breakout force @ pivot pin
23° bucket roll back
43° dump angle

THE FARMALL 65A AND 75A MODELS USE THE L540 FRONT LOADER

3,250 lb. (1474 kg) lift capacity @ pivot pins
126 in. (3190 mm) lift height
4,670 lb. (2118 kg) breakout force @ pivot pin
24° bucket roll back
37° dump angle

| | Farmall 45A | Farmall 55A | Farmall 65A | Farmall 75A |
|---|---|---|--|---|
| ENGINE | | | | |
| Engine Type | 4-Cylinder Diesel | | | |
| Number of Cylinders/Aspiration | 4/Natural | | 4/Turbocharged | |
| Displacement | 135 cu. in. (2.2 L) | | 195 cu. in. (3.2 L) | |
| Gross Engine/PTO HP | 45/39 | 55/47.5 | 65/57 | 75/66 |
| Rated Speed | 2700 rpm | | 2500 rpm | |
| Fuel Type | Standard diesel fuels or B5 Biodiesel (meeting ASTM6751 standards) | | Standard diesel fuels or B100 Biodiesel (meeting ASTM6751 standards) | |
| Air Filter | Dual elements, dry type with cleanable outer element and replaceable inner safety element | | | |
| Emissionization Standard | Tier III | | | |
| Fuel Tank Capacity | 13.5 gal. (51 L) | | 16.4gal. (62 L) | |
| TRANSMISSION | | | | |
| Traction Clutch | Dry, 11-inch (279.4mm) diameter organic plate | | | |
| Base on Standard Tractor | 8F x 8R w/4 constant mesh gears, 2 constant mesh ranges & synchronized shuttle | | 8F x 2R w/4(2 synchronized) gears & 2 constant mesh ranges | |
| Tire Size: 2WD - Front | 6x16, 6PR(F2) | | 7.5x16, 6PR(F2) | |
| - Rear | 12.4x28, 6PR(R1) | 14.9x28, 6PR(R1) | 16.9x30, 6PR(R1) | |
| 4WD - Front | 8.3x24, 6PR(R1) | 9.5x24, 6PR(R1) | 11.2x24, 6PR(R1) | |
| - Rear | 13.6x28, 6PR(R1) | 14.9x28, 6PR(R1) | 16.9x30, 6PR(R1) | |
| BRAKES | | | | |
| Service/Parking Brakes | Individual mechanically activated wet disc/ Engage hand-lever, front-assist service brake | | | |
| REAR AXLE | | | | |
| Rear Differential Lock | Mechanical foot pedal engagement | | | |
| FRONT AXLE | | | | |
| Front Differential Lock | Limited Slip | | | |
| FWD Clutch Engagement | Mechanical Lever | | | |
| HYDRAULICS | | | | |
| System Type | Open center, fixed displacement gear pump | | | |
| Implement Pump Capacity | 11.6 gpm (44 L/min.) | | 10.4 gpm (39.3 L/min.) | |
| Steering & Services System | Hydrostatic power steering w/dedicated gear pump 5.3 gpm (20.1 L/min.) | | Hydrostatic power steering w/dedicated gear pump 8.5 gpm (32 L/min.) | |
| Total Maximum Tractor Flow | 16.9 gpm (64.1 L/min.) | | 18.7 gpm (71.3 L/min.) | |
| Remote Valves | Standard 1 open center, rear mounted, opt second remote available | | | |
| REAR 3-POINT HITCH | Standard, Category II/I | | | |
| Position Control, Draft Sensing | One level, no draft control | | One lever, standard mechanical draft control | |
| DECD Lift Capacity @ 24" Behind Ball Ends | 1830 lbs. (830 kg) | 2580 lbs. (1170 kg) | 2954 lbs. (1340kg) | |
| Rear PTO | Standard 540-RPM, w/flip-up PTO shaft guard | | | |
| ELECTRICAL | | | | |
| Alternator | 12 volt, 40 amp | 12 volt, 55 amp | 12 volt, 65 amp | |
| Battery Capacity (Cold Cranking Amps) | 800 | | | |
| Lighting | 2hi/lo beam halogen headlights, flashing safety lights/turn signals | | | |
| Accessory Power Outlets | Standard equipment, 7-pin implement outlet | | | |
| GENERAL | | | | |
| ROPS | Foldable | | | |
| Approx. Shipping Weight, : 2WD/4WD | 3527 lbs. (1600 kg.)/ 3836 lbs. (1740 kg.) | 3770 lbs. (1710 kg.)/ 4078 lbs. (1850 kg.) | 5059 lbs. (2295 kg.)/ 5688 lbs. (2580 kg.) | 5059 lbs. (2295 kg.)/ 5688 lbs. (2580 kg.) |
| Approx. Shipping Length, : 2WD/4WD | 131.1 in. (3331 mm.)/ 133.5 in. (3390 mm.) | 131.1 in. (3331 mm.)/ 133.5 in. (3390 mm.) | 137.2 in. (3483 mm.)/ 139.6 in. (3543 mm.) | 137.2 in. (3543 mm.)/ 139.6 in. (3543 mm.) |
| Approx. Shipping Width, : 2WD/4WD | 66.1 in. (1680 mm.)/ 66.1 in. (1680 mm.) | 67.7 in. (1720 mm.)/ 67.7 in. (1720 mm.) | 78.4 in. (1990 mm.)/ 78.4 in. (1990 mm.) | 78.4 in. (1990 mm.)/ 78.4 in. (1990 mm.) |
| Approx. Shipping Height, : 2WD/4WD | 93.9 in. (2385 mm.)/ 93.9 in. (2385 mm.) | 95.9 in. (2435 mm.)/ 95.9 in. (2435 mm.) | 96.9 in. (2460 mm.)/ 96.9 in. (2460 mm.) | 96.9 in. (2460 mm.)/ 96.9 in. (2460 mm.) |



SAFETY NEVER HURTS!TM Always read the Operator's Manual before operating any equipment. Inspect equipment before using it, and be sure it is operating properly. Follow the product safety signs, and use any safety features provided. CNH America LLC reserves the right to make improvements in design and changes in specifications at any time without notice and without incurring any obligation to install them on units previously sold. Specifications, descriptions and illustrative material herein are as accurate as known at time of publication, but are subject to change without notice. Availability of some models and equipment builds varies according to the country in which the equipment is used.

©2011 CNH America LLC. All rights reserved. Case IH is a registered trademark of CNH America LLC. Any trademarks referred to herein, in association with goods and/or services of companies other than CNH America LLC, are the property of those respective companies. Printed in U.S.A. www.caseih.com

CIH0xxxxxx