

GR20 Series

Specifications

GR2020 – GR2120



| Model | | GR2020G | GR2120 |
|---|-------------|--|-----------------------------------|
| Engine | | | |
| Model | | GH631 | D782 |
| Type | | 2 cylinders, gasoline, air cooled | 3 cylinders, diesel, water-cooled |
| Total displacement | cu.in. (cc) | 39.1 (624) | 47.5 (778) |
| Gross horsepower | HP (kW) | 20.5 (15.3)* ¹ | 21.0 (15.6)* ² |
| Engine layout | | Horizontal | |
| Fuel tank capacity | gal. (ℓ) | 4.2 (16) | 4.8 (18) |
| Dimension | | | |
| Overall length | inch (mm) | 77.2 (1960) | |
| Overall width (with 48" / 54" mower deck) | inch (mm) | 61.0 (1550) / – | 61.0 (1550) / 66.9 (1700) |
| Overall height | inch (mm) | 50.8 (1290) | |
| Wheelbase | inch (mm) | 50.4 (1280) | |
| Tread | | | |
| Front/Rear | inch (mm) | 32.5 (825) / 31.5 (800) | |
| Weight (with 48" / 54" mower deck) | lbs. (kg) | 882 (400) / – | 959 (435) / 970 (440) |
| Tire size | | | |
| Front/Rear | | 16 × 7.5–8 / 23 × 10.50–12 | |
| Transmission | | Hydrostatic transmission | |
| Transmission drive | | Shaft drive | |
| Speed control | | Single foot pedal | |
| Traveling speed | | | |
| Forward/Reverse | mph (km/h) | 0–6.2 (0–10.0) / 0–3.1 (0–5.0) | |
| Cruise control | | Std. | |
| Brake | | Internal expanding brake | |
| PTO clutch | | Hydraulic wet multi discs | |
| Mower deck drive | | Shaft drive | |
| Steering system | | Glide Steer, hydraulic power steering | |
| Operator's deck | | Flat | |
| Seat adjustment | | Slide | |
| Seat suspension | | Mechanical suspension with weight adjustment | |
| Fuel gauge | | Std. | |
| Hour meter | | Std. | |
| Easy checker | | Std. | |
| Mower OPC. | | Std. | |
| Travel OPC. | | Std. | |
| Blade shut off brake | | PTO Clutch | |
| Grass catcher (optional) | | | |
| Capacity | bushel | 10 | |
| Material of bag | | cloth | |

Mower Specifications

| | | | |
|------------------------------------|-----------|------------------|-----------------------|
| Cutting width | inch (mm) | 48 (1219) | 48 (1219) / 54 (1372) |
| Lifting device | | Hydraulic | |
| Mower mounting method | | Parallel linkage | |
| Cutting height | inch (mm) | 1.0–4.0 (25–102) | |
| Cutting height adjustment | | Dial gauge | |
| Cutting height increments | | 1/4" | |
| Number of blades | | 3 | |
| Direction of discharge | | Right side | |
| Minimum uncut diameter | inch (mm) | 43 (1100) | 43 (1100) / 35 (900) |
| Mower deck ground clearance | inch (mm) | 5.5 (140) | |

* Power (hp) specifications for individual gasoline engine models are rated pursuant to Society of Automotive Engineers (SAE) J1940 based on gross output testing performed in accordance with SAE J1995 without the air cleaner and muffler. Gross engine hp will be higher than actual engine power which is affected by accessories, application, engine speed, ambient operating conditions and other factors. The gross engine horsepower information is for comparison purposes only.

* SAE J1995