

TE Series

Specifications

TE6576CD / TE8511C



Kubota Models	TE6576CD	TE8511C
FarmLine	-	-
ProLine	•	•
Dimensions & Weight		
Working width* (ft)	24'11"	36'1"
Width, working position (ft)	25'7"	37'1"
Transport width (ft)	9'9"	9'9"
Transport length (ft)	14'9"	19'6"
Storage height (ft)	13'2"	10'10"
Weight approx. (lbs)	2646	3957
Capacity theor. (acres/h)	15.1	21.7
Attachment		
Three-point, tracking	-	-
Linkage drawbar	-	-
Two-point, linkage arms	Cat. II	Cat. II
Vibration damper/integral lock	-	-
Rotors/Tines/Guard		
No. of rotors	8	8
No. of tine arms / rotor	7	7
Tine adjustment system	•	•
Adjustment of spreading angle	•	•
Cab contr. border clearing system, Mech.	-	-
Cab contr. border clearing system, Hydr.	•	•
Reduc. gearbox for night swaths	o	o
Tires/Axles/Lights		
Wheels	16x6.5-8	16x6.5-8
Tires on central unit	18.5x8.5-8	18.5x8.5-8
Front wheel (16x6.50-8)	•	-
Tandem axles	-	-
Warning panels	-	-
Warning panels with integr. lighting	•	•
• = standard o = optional - = not available		
*(DIN 11220)		

The company reserves the right to change the above specifications without notice. This brochure is for descriptive purpose only. Some of the items pictured in this brochure are optional and not standard equipment. Please consult your local Kubota dealer for warranty, safety or product information. For your safety, Kubota strongly recommend the use of a seat belt in all applications.