

# Z700 Series

# Specifications

Z723 - Z724 - Z725 - Z724X - Z726X



| Model                      |                         | Z700                        |  |              |                       |                       |              |                       |
|----------------------------|-------------------------|-----------------------------|--|--------------|-----------------------|-----------------------|--------------|-----------------------|
|                            |                         | Z724XKW-48                  | Z724XKW-54                             | Z726XKW-60   | Z723KH-48             | Z724KH-54             | Z725KH-60    |                       |
| <b>Engine</b>              | Model                   | GH735V                      |  |              |                       |                       |              |                       |
|                            | Type                    | Gasoline, air-cooled V-Twin |  |              |                       |                       |              |                       |
|                            | Max. horsepower (Gross) | HP                          | 23.5*                                  | 25.5*        | 22.5**                | 23.5**                | 25**         |                       |
|                            | Total displacement      | cu. in. (cc)                | 44 (726)                               | 52 (852)     | 42 (694)              |                       | 46 (747)     |                       |
|                            | Starting system         | Key switch                  |  |              |                       |                       |              |                       |
| <b>Dimensions</b>          | Overall length          | in. (mm)                    | 83.9 (2130)                            |              |                       |                       |              |                       |
|                            | Overall width           | (w/ mower) in. (mm)         | 61.3 (1557)                            | 67.3 (1710)  | 73.8 (1875)           | 61.3 (1557)           | 67.3 (1710)  | 73.8 (1875)           |
|                            |                         | (w/o mower) in. (mm)        | 50.4 (1280)                            |              | 54.7 (1390)           | 50.4 (1280)           |              | 54.7 (1390)           |
|                            | Overall height          | (w/ ROPS upright) in. (mm)  | 69.9 (1775)                            |              |                       |                       |              |                       |
|                            |                         | (w/ ROPS folded) in. (mm)   | 48.3 (1226)                            |              |                       |                       |              |                       |
| <b>Wheel base</b>          |                         | in. (mm)                    | 50.9 (1294)                            |              |                       |                       |              |                       |
| <b>Tread</b>               | Front                   | in. (mm)                    | 37.6 (954)                             |              |                       |                       |              |                       |
|                            | Rear                    | in. (mm)                    | 40.2 (1020)                            |              | 42.6 (1083)           | 40.2 (1020)           |              | 42.6 (1083)           |
| <b>Tire size</b>           | Front                   |                             | 13 x 5.0 - 6 Non flat                  |              | 13 x 6.5 - 6 Non flat | 13 x 5.0 - 6 Non flat |              | 13 x 6.5 - 6 Non flat |
|                            | Rear                    |                             | 24 x 9.5 - 12                          |              | 24 x 12 - 12          | 24 x 9.5 - 12         |              | 24 x 12 - 12          |
| <b>Weight (w/ mower)</b>   |                         | lbs. (kg)                   | 1163.0 (527)                           | 1179.0 (535) | 1232.0 (559)          | 1168.4 (530)          | 1181.7 (536) | 1212.5 (550)          |
| <b>Transmission</b>        |                         |                             | Parker Torqpack GT14                   |              |                       |                       |              |                       |
| <b>Transmission system</b> |                         |                             | 1 HST - G rotor type                   |              |                       |                       |              |                       |
| <b>Speed control</b>       |                         |                             | 2-hand lever                           |              |                       |                       |              |                       |
| <b>Travel speed range</b>  | Forward                 | mph (km/h)                  | 0-11.2 (0-18)                          |              |                       |                       |              |                       |
|                            | Reverse                 | mph (km/h)                  | 0-5.6 (0-9)                            |              |                       |                       |              |                       |
| <b>Brake type</b>          |                         |                             | Drum disks, foot applied, released     |              |                       |                       |              |                       |
| <b>PTO</b>                 | Type                    |                             | Belt drive                             |              |                       |                       |              |                       |
|                            | Clutch type             |                             | Electric clutch                        |              |                       |                       |              |                       |
|                            | PTO brake               |                             | Dry disc                               |              |                       |                       |              |                       |
| <b>Mower deck</b>          | Model                   |                             | RCK48P-723Z                            | RCK54P-724Z  | RCK60P-725Z           | RCK48P-723Z           | RCK54P-724Z  | RCK60P-725Z           |
|                            | Mower lift system       |                             | Mechanical                             |              |                       |                       |              |                       |
|                            | Mower deck type         |                             | Commercial fabricated deck             |              |                       |                       |              |                       |
|                            | Deck depth              | in. (mm)                    | 6.0 (152)                              |              |                       |                       |              |                       |
|                            | Belt type               |                             | Single belt                            |              |                       |                       |              |                       |
|                            | Deck steel thickness    | Ga (mm)                     | 8 (4.18)                               |              |                       |                       |              |                       |
|                            | Anti-scalp roller       |                             | Rigid                                  |              |                       |                       |              |                       |
|                            | Cutting width of mower  | in.                         | 48 (1219.2)                            | 54 (1371.6)  | 60 (1524)             | 48 (1219.2)           | 54 (1371.6)  | 60 (1524)             |
|                            | Number of blades        |                             | 3                                      |              |                       |                       |              |                       |
|                            | Cutting height          |                             | 1.0 in. - 5.0 in. 1/4 in. increments   |              |                       |                       |              |                       |
|                            | Mower mounting system   |                             | Parallel linkage                       |              |                       |                       |              |                       |
|                            | Blade tip speed (max.)  | FPM                         | 18100                                  |              |                       | 18600                 |              |                       |
| <b>Engine stop system</b>  |                         |                             | Key stop                               |              |                       |                       |              |                       |
| <b>Fuel tank capacity</b>  |                         | gals. (ltrs.)               | 11.6 (43.9)                            |              |                       |                       |              |                       |
| <b>Battery</b>             |                         |                             | U1 (12V, RC: 45min, CCA: 300, CA: 410) |              |                       |                       |              |                       |
| <b>Generator capacity</b>  |                         | Amp                         | 15A                                    |              |                       |                       |              |                       |
| <b>Hour meter</b>          |                         |                             | Standard                               |              |                       |                       |              |                       |
| <b>Fuel gauge</b>          |                         |                             | Electric gauge type                    |              |                       |                       |              |                       |

\*These Kawasaki engines have been tested in accordance with SAE J1995, verified by TÜV Rheinland Group, and certified by SAE International. The gross power ratings of these engines were determined by using measurements according to SAE J1995 which were witnessed by SAE-approved witnesses from TÜV Rheinland Group. Torque ratings of these engines were not certified by SAE. Actual power and torque output will vary depending on numerous factors, including, but not limited to, the operating speed of the engine in application, environmental conditions, maintenance, and other variables.

\*\*Power (hp) specifications for individual gasoline engine models are rated pursuant to Society of Automotive Engineers (SAE) J1940 based on gross output testing performed in accordance with SAE J1995 without the air cleaner and muffler. Gross engine hp will be higher than actual engine power which is affected by accessories, application, engine speed, ambient operating conditions and other factors. The gross engine horsepower information is for comparison purposes only.

The company reserves the right to change the above specifications without notice. Please contact your local Kubota dealer for warranty information. For your safety, Kubota strongly recommends the use of a roll over protective structure (ROPS) and seatbelt in almost all applications.