

# ZD1200 Series

# Specifications

ZD1211-60 - ZD1211-72



Model		ZD1211		ZD1211L			
		ZD1211-60	ZD1211R-60R	ZD1211L-72	ZD1211RL-72R		
<b>Engine</b>	Model	Kubota D1105-E4-ZD-2					
	Type	Diesel, liquid-cooled(3 cyl.)					
	Max. horsepower (Gross)*	HP	24.8@3000rpm				
	Total displacement	cu.in. (cc)	68.53 (1123)				
	Starting system	Key switch					
<b>Dimensions</b>	Overall length	in. (mm)	89.0 (2260)		93.7 (2380)		
	Overall width	(w/ mower)	in. (mm)	73.8 (1875)	63.0 (1600)	85.8 (2180)	75.2 (1910)
		(w/o mower)	in. (mm)	59.4 (1510)		60.6 (1540)	
	Overall height	(w/ ROPS upright)	in. (mm)	78.7 (200)			
		(w/ ROPS folded)	in. (mm)	64.6 (1640)			
<b>Wheel base</b>		in. (mm)	56.7 (1440)		61.4 (1560)		
<b>Tread</b>	Front	in. (mm)	41.9 (1064)		49.2 (1250)		
	Rear	in. (mm)	47.6 (1210)				
<b>Tire size</b>	Front	15 × 6.0-6, Smooth semi-pneumatic					
	Rear	26 × 12.0-16, Low profile tire					
<b>Weight (w/ mower)</b>		lbs. (kg)	1676 (760)	1687 (765)	1742 (790)	1775 (805)	
<b>Transmission system</b>	2-HST w/ Gear reduction						
<b>Speed control</b>	2-hand levers						
<b>Travel speed range</b>	Forward	mph (km/h)	0-10.6 (0-17.0)				
	Reverse	mph (km/h)	0-5.3 (0-8.5)				
<b>Brake type</b>	Wet multi disks, foot applied, released						
<b>PTO</b>	Type	Shaft drive					
	Clutch type	Hydraulic independent PTO clutch with wet multi disks					
	PTO brake	Wet single disk					

# ZD1200 Series

# Specifications

ZD1211-60 - ZD1211-72



Mower deck	Model	RCK60P-1200Z	RCK60RP-1200Z	RCK72P-1200Z	RCK72RP-1200Z
Mower deck type		Kubota ProDeck with ACS	Kubota ProDeck	Kubota ProDeck with ACS	Kubota ProDeck
Mower lift system		Hydraulic			
Deck depth	in. (mm)	6.0 (152.4)	5.5 (140)	6.0 (152.4)	5.5 (140)
Belt type		Multi-belt			
Deck steel thickness	in. (mm)	0.16 (4.2)			0.18 (4.5)
Anti-scalp roller		Swivel			
Cutting width of mower		60 (1524)		72 (1829)	
Number of blades		3 blades			
Cutting height	in. (mm)	1-5 (25-127)			
Mounting system of mower		Quick joint, parallel linkage			
Blade tip speed (max.)	FPM	18050	16900	18050	18000
<b>Seat</b>		Deluxe suspension seat with Reclining and Lumber Support			
<b>Engine stop system</b>		Key stop			
<b>Fuel tank capacity</b>	gals. (ltrs.)	12.9 (48.8)			
<b>Battery</b>		Maintenance free battery : 12 V, CCA : 430A , RC : 80 min			
<b>Alternator capacity</b>		AC Dynamo : 14 Amps @ 14 Volts			
<b>Water temperature indicator</b>		Standard			
<b>Hour meter</b>		Standard			
<b>Fuel gauge</b>		Standard			

\* Power(HP) specifications for individual diesel engine models are rated pursuant to Society of Automobile Engineers(SAE) J1940 based on gross output testing performed in accordance with SAE J1995 without the air cleaner and muffler. Diesel engine hp will be higher than actual engine power which is affected by accessories, application, engine speed, ambient operating conditions and other factors. The gross engine horsepower information is for comparison purpose only. The company reserves the right to change the above specifications without notice. This brochure is for descriptive purposes only. Please contact your local Kubota dealer for warranty information. For your safety, Kubota strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications.